

now professional
photography



goes **AUTOMATIC**
with the magnificent
MAMIYAFLEX C33
www.ianbfoto.com

world's only interchangeable lens twin-lens reflex
with automatic features!

For professional photographers all over the world, Mamiyaflex represents the ultimate standard in twin-lens reflex cameras. And now Mamiya proudly present the Mamiyaflex

C33 — world's only twin-lens reflex with interchangeable lenses *and* automatic shutter cocking . . . automatic parallax compensation indicator.

Based on the superb Mamiyaflex C3, this versatile new camera features . . .

FIVE INTERCHANGEABLE LENSES

From wide angle to tele-photo. And you change them as readily as on a 35mm

camera! Range is 65mm. f/3.5, 80mm. f/2.8, 105mm. f/3.5, 135mm. f/4.5 and 180 mm. f/4.5.

INTERLOCKED AUTOMATIC FILMWIND AND SHUTTER COCKING

Simultaneous shutter cocking and film transport preclude accidental multiple

exposures. Rapid crank action is smooth and positive.

AUTOMATIC PARALLAX COMPENSATION INDICATOR

Pointer on ground glass viewing screen indicates exact upper limit of picture . . .

operates by setting simple parallax compensation dial to lens in use.

EXPOSURE FACTOR SCALE

For close range photography, parallax compensation pointer also indicates the compensation factor that must be applied

to allow for reduced light input from narrowed subject coverage.

BUILT-IN BELLOWS FOR EXTREME CLOSE-UPS

Super extension allows up to 60mm beyond normal position. With the 65mm wide-angle lens subjects only 4 in. from the lens

can be photographed without auxiliary equipment.

PERFECT FILM FLATNESS

The conventional "L" bend necessary in most cameras is eliminated . . . perfect

flatness assures precise register on all points of film.

SINGLE FRAME EXPOSURE WITH CUT FILM

Exchange easily-removed standard back for special cut film/plate-holder back, for

immediate processing of economic single shots.

EYE-LEVEL VIEWING

An open-frame viewfinder is incorporated in the collapsible viewfinder hood. The additional use of a PORROFLEX eye-

level attachment permits eye-level viewing of any correctly oriented image.

Additional Specification

SHUTTER SEIKOSHA S. with B, and 1 — 1/500 second; full flash synchronization

at all shutter speeds, automatic shutter cocking, thumb-operated release.

FILM 120 film, 12 exposure (6 x 6 cm) per roll.

FOCUSING By viewfinder image; dual

knob rack and pinion extension mechanism.

FILM COUNTER Automatic reset type.

VIEWFINDER HOOD Interchangeable; equipped with magnifier, built-in masks for

65mm and 80mm open-frame viewer; studs for 105mm to 180mm frames.

Distributed, Serviced, guaranteed by



www.ianbfoto.com

THE RANK ORGANISATION
PHOTOGRAPHIC HOUSE · 11 AINTREE ROAD
PERIVALE · MIDDLESEX