Interchangeable Finder System

There are four types of interchangeable finders for the Pro-SD which can be quickly changed to meet various photographic applications. In particular, the PD Prism Finder with its built-in-electronic circuitry is a significant advance in medium format photography. There also are seven types of focusing screens that can be applied to a multiplicity of compositions.



	Waist-Lavel Finder	Prism Finder Model 2	PD Prism Finder		
Туре	Opens and closes at a single touch (Shielded with magnifier)	Viewing angle 30 'dowr; unreversied, laterally correct image eve-level finder			
Metering			Average (Al/spot (5) zero-method selection TTL exposure measurement at open aperture		
Metering range	-		EV3.6 (t/3.5 at 1 sec.) to EV 18.5 (t/32, 1/400 sec.) with 127mm (t/3.5 ISO 100		
Shutter speed range	M 1		1-1/400 sec. reading system		
Aperture range			2.8-45 reading system		
Finder information	-		Glowing or blinking digital diaplay with red, orange or green LES		
Coupled film speed			ISO 12-6400		
Spot metering area	_		7.3% of picture area in the center		
Magnification	1.5x (magnifier magnificatio 3x) with 127mm t/3.5 ~	09x(#	0.9 x (magnifier magnification 1.8 x) with 127mm (/3.5 ~		
Diopter correction	Standard -1.3 diopter; 6 type of diopter lens from +1 to -3 diopter	8 types of eye correction lens (+34 diopter)			
Power source		-	6V elkaline mangenese battery 4LR44 or 6.2V silver code better 4SR44 (x1)		
Weight	1509	880g	920g (without battery)		

terchangeable Roll Film Holder System

vith the 6 × 7cm format and Polaroid nack film h



	120 Roll Film Holder (HA701)	ZZU Hott Fifth Hotter (HB701)	120/220 Power Drive Roll Film Holder 6x7	128/228 Power Drive Roll Film Holder 6x8	120 Rett Film Holder 6x4.5(HA702) (with Special Finder Mask)	6x4.5(HB704) (with Special Finder Mask)	Polaroid Pack Film Holder (HP701)
Film type	120 roll film	220 roll film	120 or 220 roll film	120 or 220 roll film	120 roll film	220 roll film	Polarcid 100-660 Series
Actual picture erea	6x7cm format (56x69.5mm)		6x8cm format (56x76mm) (56x75mm)	6x4.5cm format (56x41.5mm)	. 6x4.5cm format (56x41.5mm)	7x7cm format (69.5x69.5mm)	
Number of exposures	10	20	10(120) or 20(220)	9(120 for 18(220)	15	30	1
Film advance system	One-stoke lever film advance Automatic film advance			ce after shutter release One-stoke lever film advance		Peel apart system	
		1000 E-000 M					
	Double exposure prevention system with warning indicator and multiple exposure lever Automatic film wind-stop release; can also be manually operated. Double exposure warning indicator film wide-stop release by manual						-
Other features	Safety dark slide lock When the dark slide is inserted in its impossible to accidentally release the shutter A safety system prevents the dark slide from being re-moved					-	
Power source	-		Alkaline m	nanganese battery or Ni-Cd battery x 4			-
Weight	475g	475g	550g(without battery)	550g(without battery)	470g	470g	320g

A total of seven types of focusing screens is available which can be changed according to photographic requirements, lens used and subject condition. Weight: 50g each

Description	Specification	Application
Type A Matte	All matte with Fresnel lens.	For general photography.
Type A 6 x 8,Matte	All matte with Fresnel lens.	For 6 x 8 Power Drive.
Type A4 Checker	Entirely matted with Fresnel lens and sectional grid markings.	Grid markings are added to the Type A. Convenient in arranging composition. Most suitable for close-ups, copying, and photographing buildings.
Type B Range-finder spot	Entirely matted with Fresnel lens and split prism at center.	For general photography. Convenient for guick, accurate focusing with the central split prism. Focusing can also be done in the surrounding matte area.
Type C Micro-Prism	Entirely matted with Fresnel lens microprism at center.	For general photography. Convenient for quick, focusing with the central microprism. Focusing can also be done in the surrounding mette area.
Type D Cross-hair	Entirely matted . Center small circular portion is transparent with cross hairs marker.	For special photography, Suitable for high magnification close-up or telephoto photography, using parallax focusing.
Type E Range-finder spot 45°/Micro-Prism	Entirely matted with Fresnel lens and diagonal split prism at center and microprism surrounding the center.	For general photography. Convenient for quick, accurate fo- cosing with either the central split prism or a doughnut- shaped microgrism. The diagonal split prism permits easy fo- cusing for both lateral and vertical lines of subject. Pocusing can also be done in the surrounding matte area.

Auto Extension Tubes for the Pro-SI The 45mm (NA701) and 82mm (NA702)

82mm (NA702)
Simply couple the tubes to the automatic diaphragm of the lens; when used in combination with the bellows extension, ultra close-ups are at your fingertips.
For example, by combining the 82mm with the standard 127mm f3.5, life size close-ups can be obtained. Weight: 43mm (370g), 82mm (490g)

Lons	Extension Tube	Magnification	Subject Distance (em)	Area Covered (sm)
KL 65mm t/4L	45mm	0.68~1.39	8.7~ 3.9	(8.2x10.2)~(4.1x5.0)
KL 75mm t/3.5L	45mm	0.60~1.21	12.8~ 6.4	(9.4x11.7)~(4.7x5.8)
	45mm	0.59~1.20	20.0~10.7	(11.3x14.1)~(5.6x7.0)
KL 90mm f/3.5L	82mm	0.90~1.41	11.7~ 8.1	(6.2x 7.7)~(4.0x5.0)
	45mm+82mm	1.39~1.90	8.1-6.4	(4.0x 5.0)~(3.0x3.7)
	45mm	0.35-0.72	41.6-23.4	(15.8x19.6)~(7.8x9.7)
KL 127mm 1/3.5L	82mm	0.65~1.01	25.4~18.3	(8.7×10.8)~(5.6×6.9)
RE IZIMIN (S.SE	45mm+82mm	1.00~1.36	18.4~15.0	(5.6x 7.0)~(4.1x5.1)
	45mm	0.32~0.64	52.2~29.7	(17.6x21.9)~(8.7x10.8)
Macro KL 140mm 54.5 Mt-A	82mm	0.58-0.90	32.1-23.3	(9.7x12.0)-(6.2x7.7)
WE LAGITH SA'D WE'N	45mm+82mm	0.90-1.22	23.4-19.2	(6.3x 7.8)~(4.6x5.7)
	45mm	0.30-0.61	59 5-34 1	(18.7x23.2)~(9.3x11.5)
KL 150mm f/3.5 L	82mm	0.55-0.85	36.8-26.9	(10.3x12.7)~(6.6x8.2)
	45mm+82mm	0.85~1.15	87-39 128-64 200-107 117-8: 61-64 416-234 25.4-18-3 18.4-15-0 52-29-7 32-1-23 23-4-19-2 56-5-28-6 56-2-5-8-6 56-2-5-8-6 56-2-5-8-6 56-2-5-1 1607-93-0 1003-7-8	(6.6x 8.2)~(4.9x6.0)
	45mm	0.25~0.51	84.5-48.7	(22.2x27.6)~(11.0x13.6)
KL 180mm f/4.5 L-A	82mm	0.46-0.72	52.5~38.6	(12.2x15.1)~(7.8x9.7)
	45mm+02mm	0.71-0.97	38.8-32.1	(7.9× 9.8) -(5.8×7.2)
	45mm	0.18~0.37	160.7~93.0	(30.6x37.9)-(15.1x18.8)
KL 250mm f/4.5 L-A	82mm	0.33-0.52	100.3-73.8	(16.8x20.8)~(10.7x13.3)
	45mm+82mm	0.52~0.71	74.2-61.6	(10.8x13.4)~(8.0x9.9)

Interchangeable Lens System

There are 18 interchangeable lenses that fit the RB67 Pro-SD from wide-angle to telephoto and speciality lenses. They include the advanced APO lenses that may be said a crystallization of Maniya's optical technology, and the Maniya KL lenses which have been specifically developed for the Pro-SD and feature abundant peripheral light transmission to assure a sharp image over the entire 6 x 7cm picture area. Wide-angle and standard 90mm lenses feature a built-in floating mechanism for more accurate focusing - thus satisfying even the most demanding professional needs.





Bellows Lens Hood G-3

Hoods

Bellows Lens Hood G-2 Bellows Lens Hood G-2
Attached to the front accessory thread of the lens, the light-weight and Heable G-2
proceedings of the Heable G-2
procedings of the Heable

Bellows Lens Hood G-3
The light-weight, flexible G-3 provides enhanced protection from extraneous light, and easily attached to the from accessor, and the control of the c

Gelatine Filter Holder Model 2

A special holder for 3-inch (7.6cm) gelatine filters; attached to 50mm to 350mm lenses. Weigh: 45g

RB/RZ Magnifier (for Prism Finder)
Attached to the PD Prism Finder or Prism
Model 2, it assures enhanced precision
focusing by magnifying the central portion of
the screen. It also features built-in diopter
correction. Weight: 70g

Front Hood for the G-3
Used in combination with the Bellows Lens
Hood G-3, the Front Hood prevents direct
light from affecting the signetter. Side to tigether, the maximum in effectiveness is
assured in photo quality. Lenses from
127mm to 350mm can be used in this
combination. The hood has a slot for
inserting a vignetter.
Maximum and minimum extension:
105mm and 25mm. Weight: 145g

Front Hood for the G-3

Sun Shield (also user with the RZ)

Sun shield (also user with the Hz)
The sun shield prevents reflections from reflective surfaces such as water or incidental sidelight or backlight from influencing picture quality by eliminating flare and ghost images from the film. It is easily attached to, or adjusted to fit, Lenses. Weight: 120g



Mirror Lock-up Cable Release (also used with the RZ)

A cable release with two cables one of which is served into the camera's shutter release button and the other into the lens' intror-up societ. A two-step actuated colors the mirror of the lens' introduced the society of the mirror lock-up and then release the shutter Indispensable for close-up or telephoto operations. Weight: 90g Quick-Shoe Model 2 (also used with the C330S and RZ)

When attached to a tripod beforehand, this handy accessory speeds the coupling and detachment of the camera to the tripod. The use of the quick-shoe assures the matching of both the tripod mount/universal head and the socket on the camera. Weight 235g



External Battery Case for PD Magnifying Finder and PD Prism Finder The case insulates the batteries from deterioration caused by extreme cold. Weight: 23g

Diopter Lens

Six types of Diopter Lenses are available for waist-level finders. With +1, 0, -1, -1.5 (standard spec.), -2, -3 diopter. Weight: 40g

Eye Correction Lens

These eye correction lenses are for the PD Prism Finder and Prism Finder Model 2, and are attached to the inner frame of the finder's rubber eyepiece. With +3, +2, +1, -0.5, -1, -2, -3, -4 diopter. Weight: 5g

Filter

77∅ screw-in type: UV, SL, PL. 105∅ screw-in type: UV, SL.

Cases Soft Camera Case

Capable of accommodating your camera while a 65mm, 90mm or 127mm is mounted on it, the case is helpful during outdoor photography and for protecting the camera when in transit. Weight: 490g

Soft Leather Lens Case

These supple and soft case are very convenient when carrying or otherwise protecting interchangeable lenses (37 to 350mm), auto extension tubes or other accessorise.



• "Q" to "1" designated lesses and open CT 100—200mm lesses are with 8 (build) mechanism. These lesses also have wider operations on the aperture ring. Minor lock up mechanism is designed to prevent curiess or negligant resists. • \$1, 67, 75 10 5, 90 and 140mm lesses have build resist name to a less a more up as up current vertically expended and the productions of the designation of the productions of the production of the productions of the production of the productions of the production of the produc

Left Hand Grip GL701
A simple grip with an integral trigger type shutter release, Ideal for helping to stabilize shots during handheld photography. With accessory shoe.
Weight: 380g



